

# SPECIALS

Treated Planks

## Specials Wallis

1204350

186 × 18,9 cm  
14/3 mm

CE  
EN 14342-05

25 years  
Solidfloor™  
guarantee



### Packaging

Boards per pack:	8 boards
m <sup>2</sup> per pack:	2,812 m <sup>2</sup>
Weight per pack:	21 kg
Broken lengths per pack:	25% minimal 60 cm length

### Dimensions

Length:	186 cm
Width:	18,9 cm
Thickness (total):	14 mm
Top layer:	2,5-3,0 mm

### Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 14 mm ± 0,2 mm
Top layer:	2,5-3,0 mm
Height difference between the panels:	≤0,2 mm
Squareness:	≤0,2% across the width
Cup:	≤0,2% across the width
Spring:	≤0,1% over the length
Bend:	≤1% over the length

### Other Specifications

Formaldehyde emission:	E1
Insulation value:	R=0,11m <sup>2</sup> k/w
Brinell hardness:	Average HB 3.7

### Additional specifications

Bevel:	1 mm
Construction:	3-layerd
Moisture content:	7% +/- 2%
Locking system:	Click

### Instructions and Maintenance

Must not be oiled after installation.  
Maintain with Solidfloor Parquet Polish. Suitable for underfloor heating & cooling (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).



EN 14342-05