

# MINERAL DRYBACK

Mineral Dryback Ruby Nature Grade

2015996

190 x 19 cm  
7/1 mm



## Packaging

Boards per pack:	6 boards
m <sup>2</sup> per pack:	2,166 m <sup>2</sup>
Weight per pack:	28,2 kg
Number of packs on a pallet:	30

## Dimensions

Length:	190 cm
Width:	19 cm
Thickness:	Total: 7 mm, including integrated sub floor Oak veneer Top layer: 1mm SPC Mineral Core carrier: 5 mm Integrated Cork subfloor: 1 mm

## Use

Floor heating (EN12524):	Yes, up to 27C°
--------------------------	-----------------

Integrated Cork subfloor - This allows the floor to be installed directly as a floating floor on the screed without the need for an additional underlay.

## Specifications

Formaldehyde emission:	E1
Insulation value:	R=0,07m <sup>2</sup> k/w
Brinell hardness:	Average HB 3.7
Locking system:	5G
Bevel:	4-sided, micro bevel
Fire class:	Bfl-S1
VOC Emission:	A+

## Instructions and Maintenance

Does not need to be oiled after installation.  
Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values;  
production-dependent deviations cannot be avoided.