

# SPECIALS

Herringbone

Specials Vintage Seekofel Herringbone 2012436

59,2 x 14,8 cm 15/4 mm





### Packaging

Boards per pack: m<sup>2</sup> per pack: Weight per pack: Broken lenghts per pack: Packs on a pallet:

### Dimensions

Length: Width: Thickness (total): Top layer: 16 boards 1,401 m<sup>2</sup> 12 kg Not allowed 56

59,2 cm 14,8 cm 15 mm 3,5-4,0 mm

### Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 15 mm ± 0,2 mm
Top layer:	3,5-4,0 mm
Height difference between the panels: ≤0,2 mm	
Squareness:	≤0.2% across the width
Cup:	≤0.2% across the width
Spring:	≤0.1% over the length
Bend:	≤1% over the length

## Other Specifications

Formaldehyde emission: Insulation value: Brinell hardness:

### Additional specifications

Bevel: Construction: Moisture content: Locking system:

### Instructions and Maintenance

Oil immediately after installation. Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating &

cooling (visit www.solidfloor.com for more information).



1 mm 4-sided 3-layerd 7% +/- 2% Tongue and groove

