

SPECIALS

Planks



Packaging

Boards per pack: m² per pack: Weight per pack: Broken lenghts per pack: Packs on a pallet:

Dimensions

Length: Width: Thickness (total): Top layer: 6 boards 2,904 m² 25 kg 25% minimal 60 cm length 35

220 cm 22 cm 15 mm 3,5-4,0 mm

Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 15 mm ± 0,2 mm
Top layer:	3,5-4,0 mm
Height difference between the panels	: ≤0,2 mm
Squareness:	≤0.2% across the width
Cup:	≤0.2% across the width
Spring:	≤0.1% over the length
Bend:	≤1% over the length

Other Specifications

Formaldehyde emission: Insulation value: Brinell hardness:

Additional specifications

Bevel: Construction: Moisture content: Locking system:

Instructions and Maintenance

Oil immediately after installation. Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).

E1 R=0,11m2 k/w Average HB 3.7

Rounded 3-layer 7% +/- 2% Tongue and groove

