

SPECIALS

Herringbone

Specials Windsor Rustic

1204402

61 x 12,2 cm
14/3 mm

CE
EN 14342-05

25 years
Solidfloor™
guarantee



Packaging

| | |
|--------------------------|----------------------|
| Boards per pack: | 12 boards |
| m ² per pack: | 0,893 m ² |
| Weight per pack: | 9 kg |
| Broken lengths per pack: | Not allowed |

Dimensions

| | |
|--------------------|------------|
| Length: | 61 cm |
| Width: | 12,2 cm |
| Thickness (total): | 14 mm |
| Top layer: | 2,5-3,0 mm |

Dimensional tolerances according to EN13489

| | |
|---------------------------------------|------------------------|
| Length: | 0,10% |
| Width: | 0,2 mm |
| Thickness: | Total: 14 mm ± 0,2 mm |
| Top layer: | 2,5-3,0 mm |
| Height difference between the panels: | ≤0,2 mm |
| Squareness: | ≤0,2% across the width |
| Cup: | ≤0,2% across the width |
| Spring: | ≤0,1% over the length |
| Bend: | ≤1% over the length |

Other Specifications

| | |
|------------------------|---------------------------|
| Formaldehyde emission: | E1 |
| Insulation value: | R=0,115m ² k/w |
| Brinell hardness: | Average HB 3.7 |

Additional specifications

| | |
|-------------------|-------------------|
| Bevel: | 1 mm 4-sided |
| Construction: | Plywood |
| Moisture content: | 7% +/- 2% |
| Locking system: | Tongue and groove |

Instructions and Maintenance

Does not need to be oiled after installation.
Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).

