

# LOFT

## Loft Old Grey

1208330

128,5 × 24,2 cm  
Total: 8 mm

CE  
EN 14342-05

15 years  
Solidfloor™  
guarantee



### Packaging

Boards per pack:	8 stuks
m <sup>2</sup> per pack:	2,49 m <sup>2</sup>
Weight per pack:	17,4 kg

### Dimensions

Length:	128,5 cm
Width:	24,2 cm
Thickness:	Totaal: 8 mm

### Use

Usage class:	23 Intensief huishoudelijk woongebruik 32 normaal commercieel gebruik
--------------	--

### Dimensional tolerances according to EN13329

Squareness:	0,20 mm/m
-------------	-----------

### Flatness of the assembled parts

Width:	concave 0.15%, convex ≤ 0.20 %
Length:	concave 0.50 %, convex ≤ 1.00 %
Height differences:	∅ ≤ 0.10 mm, max. ≤ 0.15 mm
Openings:	∅ ≤ 0.15 mm, max. ≤ 0.20 mm

### Geometric properties

Length:	1285 ± 0.5mm
Width:	242 ± 0.1mm – bmax – bmin 0.2mm

### Specifications

Heat transfer coefficient:	R ≤ 0.07m <sup>2</sup> k/w
Lightfastness (ISO 105-B02):	Better than Level 4 Grayscale
Abrasion resistance (EN 13329):	AC4
Stain resistance:	Group 1-2 Level 5 Group 3 Level 4
Surface Structure:	Embossed
Bevel:	4-sided bevel
Locking system:	Angle-angle
Fire class:	Cfl-S1
Formaldehyde (EN 16516):	E1
VOC Emission:	A+

### Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.