

# MANSION

Herringbone

## Mansion Natural Oak

1209228

75 x 15 cm  
6/0,55 mm

CE  
EN 14342-05

25 years  
Solidfloor™  
guarantee



### Packaging

Boards per pack:	12 boards
m <sup>2</sup> per pack:	1,35 m <sup>2</sup>
Weight per pack:	16,2 kg
Number of packs on a pallet:	54

### Dimensions

Length:	75 cm
Width:	15 cm
Thickness:	Total: 6 mm Top layer: 0.55 mm

### Use

Usage class:	23 intensive domestic residential use 33 intensive commercial use
Floor heating (EN12524):	Yes, up to 27C°
Suitable for office chairs?:	Yes
Resistant to chemicals? (EN 423):	Yes, good
Acoustic reduction of impact sound:	7dB

### Specifications

Lightfastness (ISO 105-B02):	>6
Abrasion resistance (EN 660-2):	Group T
Heat transfer coefficient:	R=0,045m <sup>2</sup> k/w
Antistatic:	<2kV
Residual indentation (ISO 24343-1):	<0.05 mm
Dimensional stability:	<0.1%
Slip resistance (DIN 51130):	R9
Repetition factor:	6
Locking system:	5G
Bevel:	4-sided, painted
Fire class:	Bfl-S1
VOC Emission:	A+

### Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.